

Product Description:

The LIBRA-S is available in a variety of wattages ranging from 30W-300W. The LIBRA-S uses a patented heat dissipation design to achieve optimum efficiency. The luminaire's modules may be replaced if another application is desired. The LIBRA-S uses a die-cast aluminum housing and polycarbonate lens.



Features:

- **Application:** LED Direct Ceiling-Mounted Canopy
- **Mounting:** Surface Mounted
- **Warranty:** 5 Years
- **LED Source:** Philips Lumileds / Cree
- **Operating Temperature:** -40°F ~ 122°F
- **Housing Material:** Die cast aluminum housing with Polycarbonate plastic lens

Technical Data:

Certifications	UL
CRI	≥ 75
IP Rating	IP66
CCT	3000K ~ 6000K
Input Voltage	100-277V/220-240V/347-480V



Specifications:

Fixture Model	Total Lumens (50K)	Efficacy (lm/w)	Dimensions (inches)	Weight (lbs)
LIBRA-S-30W	3,300 lm	110 lm/W	8.7 x 13 x 5.41	7.5
LIBRA-S-60W	6,600 lm	110 lm/W	9.96 x 13 x 5.41	9.5
LIBRA-S-90W	9,900 lm	110 lm/W	12.4 x 13 x 5.41	12.3
LIBRA-S-120W	13,200 lm	110 lm/W	14.84 x 13 x 5.41	13.9
LIBRA-S-150W	16,500 lm	110 lm/W	17.28 x 13 x 5.41	16.1
LIBRA-S-180W	19,800 lm	110 lm/W	19.72 x 13 x 5.41	18.3
LIBRA-S-210W	23,100 lm	110 lm/W	22.17 x 13 x 5.41	20.5
LIBRA-S-240W	26,400 lm	110 lm/W	24.61 x 13 x 5.41	22.7
LIBRA-S-270W	29,700 lm	110 lm/W	27.05 x 13 x 5.41	24.9
LIBRA-S-300W	33,000 lm	110 lm/W	29.5 x 13 x 5.41	27.1

Ordering Guide:

LIBRA-S-300W	120-277V	BL	SM	50K	T5M
Wattage: 30W 60W 90W 120W 150W 180W 210W 240W 270W 300W	Voltage: 120-277V 220-240V 347-480V	Color: BL: Black GR: Grey WH: White	Mount: SM: Surface Mount	CCT: 30K 40K 50K 60K	Beam Angle T1S: Type 1 Short 95° x 85° T1M: Type 1 Medium 143° x 95° T5M: Type V Medium 75° x 75°