

### Product Description:

The Dusk to Dawn LED fixture of the future is here. This luminaire utilizes a single COB source LED and provides prismatic designed light output for any environment. The AURA utilizes the latest generation of LEDs and is equipped with a NEMA approved photo control for significant power savings. The Night-time - ON and Daylight-OFF setting provides a reliable security solution for pathways, barns, and side roads.



### Features:

- **Application:** LED Dusk to Dawn
- **Mounting:** Slipfitter (1.18"-1.85") / Wall Mount
- **Warranty:** 5 Years
- **Lens:** Polycarbonate lens
- **LED Source:** Cree XPG
- **Operating Temperature:** -40°F ~+ 131°F
- **Housing Material:** Die cast aluminum



### Technical Data:

<b>Certifications</b>	<b>UL</b>
<b>CRI</b>	<b>≥ 75</b>
<b>IP Rating</b>	<b>IP65</b>
<b>CCT</b>	<b>3000K ~ 5000K</b>
<b>Input Voltage</b>	<b>120-277V</b>




### Specifications:

Fixture Model	Total Lumens (T5)	LED Quantity	Dimensions (inches)	Weight (lbs)	Certs
AURA-20W	2,565.1 lm	10 pcs	15.2 x 14.4 x 3.6	14.3	UL
AURA-30W	3,788.2 lm	15 pcs	20 x 14.4 x 3.6	17.6	
AURA-50W	6,123.5 lm	25 pcs	20 x 14.4 x 3.6	17.6	

# Photometrics

**AURA-10W**




**Illuminance at a Distance**

Center Beam fc	Beam Width
9.7ft	3.37 fc 22.8 ft 22.6 ft
19.3ft	0.85 fc 45.3 ft 45.0 ft
29.0ft	0.38 fc 68.1 ft 67.6 ft
38.7ft	0.21 fc 90.9 ft 90.2 ft
48.3ft	0.14 fc 113.4 ft 112.6 ft
58.0ft	0.09 fc 136.2 ft 135.2 ft

Vert. Spread: 99.2°  
Horiz. Spread: 98.7°

**AURA-20W**




**Illuminance at a Distance**

Center Beam fc	Beam Width
9.7ft	6.82 fc 22.4 ft 22.2 ft
19.3ft	1.72 fc 44.5 ft 44.2 ft
29.0ft	0.76 fc 66.9 ft 66.4 ft
38.7ft	0.43 fc 89.3 ft 88.6 ft
48.3ft	0.27 fc 111.4 ft 110.6 ft
58.0ft	0.19 fc 133.8 ft 132.8 ft

Vert. Spread: 98.2°  
Horiz. Spread: 97.7°

**AURA-30W**




**Illuminance at a Distance**

Center Beam fc	Beam Width
9.7ft	9.74 fc 22.4 ft 22.7 ft
19.3ft	2.46 fc 44.7 ft 45.1 ft
29.0ft	1.09 fc 67.1 ft 67.8 ft
38.7ft	0.61 fc 89.5 ft 90.5 ft
48.3ft	0.39 fc 111.8 ft 112.9 ft
58.0ft	0.27 fc 134.2 ft 135.6 ft

Vert. Spread: 98.3°  
Horiz. Spread: 98.9°

**AURA-50W**



**Illuminance at a Distance**

Center Beam fc	Beam Width
9.7ft	15.2 fc 22.5 ft 22.5 ft
19.3ft	3.83 fc 44.9 ft 44.8 ft
29.0ft	1.70 fc 67.4 ft 67.3 ft
38.7ft	0.95 fc 89.9 ft 89.8 ft
48.3ft	0.61 fc 112.2 ft 112.1 ft
58.0ft	0.42 fc 134.8 ft 134.6 ft

Vert. Spread: 98.6°  
Horiz. Spread: 98.5°

## Ordering Guide:

